

ESTIMATE FOR INTERIOR FURNISHING WORK OF PUNJAB AND SIND BANK BO- BRANCH & ATM DERA BASSI .

Sl.	Description of Item	Qty.	Unit	Rates	Amount
A INTERIOR WORKS					
PANELING/PARTITON					
	Note: (i) For the works of paneling, full height partitons and low height partitons measurement shall be done only for plain visible surface, no extra cost for extrusions or extra frame work required will be made. The work done above ceiling, below floor finish level or not directly visible shall not be measured.				
	(ii) All ply to be sprayed with anti terminate and anti borer spray.				
	(iii) Laminate, Shades – Colour code –Century laminates - Frosty white-111, Merino 22291SF, Greenlam laminates - Mango-1208,Merino 21467SF Greenlam Laminates - Navy Blue-281, Merino 21272SF Greenlam laminates Refresh Oak 5427 ,Merino 10839SF				
	(iv) Paint shades- Absolute white -L.161, Mango Mood -X109 paint funshing as per model branch concept.				
1 WALL PANELING					
a	Providing and fixing of paneling on column/wall. Framing shall consist of Aluminium Box Sections 50mm x25 mm x1.5 mm wall thickness (0.583 Kg/m) (Make Jindal/ Hindalco/ Indal) with maximum spacing @ 600mm c/c both ways horizontally and vertically on the column/wall. This framing would be covered by 12mm HDHMR Ply (Moisture content- <8 % , Water Absorption 5% after 2 Hours Soaking)(Make. GREENPLY/ Century / Duro) and finished with 1.0 mm thk. laminate(Make- Archdiam/Century/Merino) of desired shade design and gloss of approved makes. Wooden molding, lipping etc shall be provided wherever required as per drawing in desired shade. . The work shall also include the cost of making cutouts for the electrical switches, lights, switch boxes etc. and provision for laying conduit for electrical/telephone/Data cabling etc.including cost of 3mm thick white foam sheet back of aluminium box sections, and 6" wide laminate strip below the under line of ceiling on wall 2" wide laminate strip of yellow colour on top surface of it with green colour laminate strip 4" wide below the yellow laminate strip as specified by	680.00	Sq.ft		
b	ACP SHEETS WALL PANELING Providing and fixing Aluminum Composite Panel (Makes- Alstrom/ Alucbond/ Alstone/Armstrong) as per the approved makes wall cladding with the 3mm thick PVDF coated aluminum composite panel (ACP) (0.25 mm coil thick) with frame of aluminum channels (25 x 50 x 1.5 mm), (Make Jindal/ Hindalco/ Indal) cleat angle (8 x 18 x 2mm) necessary hardware, backup material and weather Sealant (Makes- Dr.Fixit, Asian paint, Ardex Endura) the joints leak proof. The spacing for the channel along the length and spacing of cleat on the perpendicular shall	480.00	Sq.ft		
2 PARTITIONS WORK					
a FULL HEIGHT PARTITIONS:					
	Providing and fixing wooden full height partition with following specifications:	460.00	Sq.ft		
	(a) Supporting system comprising of Aluminum Frame Work of 50mm x 50mm x 1.5 mm wall thickness,(Make Jindal/ Hindalco/ Indal) square section max. 600mm c/c both horizontally and vertically. The bottom member shall be aluminum extruded section of size 50mm X 50mm X 1.5 mm wall thickness. The frame shall be fixed rigidly at floor level and ceiling level wherever possible. The rate should also include necessary strengthening with additional				
	(b) Fixing 8mm thick HDHMR ply (Moisture content- <8 % , Water Absorption 5% after 2 Hours Soaking)(Make. GREENPLY/ Century / Duro) on both sides finished both side with 1.0 mm thk. laminate(Make- Archdiam/Century/Greenlam) (premium range) of approved shade with groove pattern as per architect instructions. Grooves to be 3mm deep and 12 wide finished with mica. 12 mm thick clear float toughened glass fixed with Teak wood beading of finished size 37mm x 25mm all along the edge. All edge-to-edge glass joint to be machine cut and polished and sealed with silicon sealant. Joint shall be located strictly as shown in the drawing. All exposed				
	(c) All exposed veneer and wooden surfaces shall be PU polished including, i) finishing all nails and glue marks ii) rubbing of surfaces iii) finishing of any depressions with putty iv) finishing of putty surface v) spraying uniformly one coat of sealer v) rubbing the surface properly and if required providing repair to any visible damage / depressions etc. vi) final finish shall be given with PU polish of approved make (Makes- ICI-Dulux, Asian and MRF) in two coats, so as to give it a uniform even look				
b LOW HEIGHT PARTITONS:4'0" HT					
	Providing and fixing low height partition with following specifications:	50.00	Sq.ft		
	(a) Supporting system comprising of Aluminum Frame Work of 50mm x 50mm 1.5 mm wall thickness Square section, (Make Jindal/ Hindalco/ Indal) max. 600 mm c/c both horizontally and vertically. The bottom member shall be aluminum extruded section of size 50mmX50mmX1.5mm wall thickness frame shall be fixed rigidly at floor level and ceiling level with rawal plugs/steel lugs wherever possible. The rate should also include necessary				
	(b) The partition shall have 8mm thick HDHMR Ply (Moisture content- <8 % , Water Absorption 5% after 2 Hours Soaking)(Make. GREENPLY/ Century / Duro) fixed on both sides with screws for the entire height of the partition and finished with approved 1.0 mm Thk. Laminate (Make- Archdiam/Century/Merino) of desired shade, design and gloss on both sides. Wooden molding, lipping etc. as directed by Bank / architect shall be provided wherever required. The partition shall have skirting and intermediate bands finished with 1.00 mm laminate of desired shade, design and gloss. All teak ply/wood to be treated with wood preservative of approved ISI quality. All				
	(c) The low height partition shall have 12 mm thick Toughened glass (Makes-Modi / Asahi / Saint Gobin) with etching as per design fixed with stainless steel wall cladding profile (WCP) at bottom. All the edges of the 12mm thick glass shall be duly				
	(d) All exposed veneer and wooden surfaces shall be PU polished including, i) finishing all nails and glue marks ii) rubbing of surfaces iii) finishing of any depressions with putty iv) finishing of putty surface v) spraying uniformly one coat of sealer v) rubbing the surface properly and if required providing repair to any visible damage / depressions etc. vi) final finish shall be given with PU polish of approved make (Makes- ICI-Dulux, Asian and MRF) in two coats, so as to give it a uniform even look				
3.0 12MM THICK TOUGHENED GLASS PARTITIONS WITH ETCHING AS PER DESIGN.					
a	Providing and fixing in position 12mm clear float toughened Glass partition (Glass Makes-Modi / Asahi / Saint Gobin) with patch fittings (Makes- Godrej/Dorma/Ozone) for the full height glass partitions with etching as per design fixed with stainless steel wall cladding profile (WCP) at bottom as per the direction of the engineer-in- charge. The work to include making necessary template for all the glasses and then cutting the clear float glass to correct size, making all the necessary holes, cuts etc., then toughened the same.	135.00	Sq.ft		
	The cost to including of all hardware PATCH FITTINGS (Makes- Godrej/Dorma/Ozone) etc.Required of approved equivalent make viz. Glazing profile (32 mm x 42 mm) in mat silver colour on top, bottom and sides and top patch and bottom patch for the openable part, or as per the direction of the engineer-in-charge, along with etching with sand blasting as per design and drawing. The maximum size of each glass shall be 1200mm to 2000mm x 2400mm to 2700mm as per the site requirement. The rate is for a finished item of work etc., complete				
	The cost to include the cost of beveling and smoothing of the exposed edges of the glass.				
	Note				
	Net area from finished floor up to false ceiling height excluding the area of door / door frames (in case of doors are not included in the item) shall be measured for the purpose of payment.				
	Items no- 2.1, 2.1.2. & 2.2, For full height partitions framework shall be provided up to the bottom of slab/ Beam .				
	No extra payment shall be made for reduction in framework ,opening as indicated in the drawing or as instructed by the engineer - in - charge. Framework shall be rigidly secured to floor , walls and ceiling by dash fasteners etc. at maximum 600mm c/c				
b	12MM GLASS : Cash cabin front glass work of 12 mm thk supported with necessary studs complete in all respect as per the drawing and instruction of Architect.	45.00	Sq.ft		
3 DOORS					
a 12MM THICK TOUGHENED GLASS DOORS :MANAGER					
	Providing and fixing in position 12mm clear float toughened glass (Makes-Modi / Asahi / Saint Gobin) for door. The work to include making necessary template for all the glasses and then cutting the clear float glass to correct size, making all the necessary holes, cuts etc., and then toughening the same. The cost to include all hardware required approved make its accessories, top pivot (1nos),Bottom Patch (1Nos) center lock (1nos), 300mm glass door handles (1set) (Make Godrej/ SXL C series (Dorma)/ OPF series (Ozone) etc. as per design and drawing. The maximum size of each glass shall be as per the drawing or the direction of the Engineer-in-charge. The rate is	90.00	Sq.ft		
	b Floor spring (Make Everite/ Dorma/ Godrej) heavy duty of approved make.	3	Nos		
c HYDRAULIC DOOR CLOSER: (Make-Doorking/ everite/ Dorma/ Ebco)					
	Providing and fixing silver color (or matching with color scheme as per site) of approved make hydraulic door closer to doors complete in all respects.	2	Nos.		
d Knight latch for cash cabin door (Make Godrej/ Ebco/ Ozone)					
		1	Nos		

e	Wicket door Providing and fixing in position 35 mm solid core flush door finished with 1mm thick laminate as per design on both sides duly polished, t.w. lipping on two vertical and horizontal edges, The flap door shall have double action door hinges and a tower bolt at suitable location.	24.00	Sq.ft		
4 FALSE CEILING					
a	GYPSTUM BOARD FALSE CEILING WITH STEPS:(Makes-Gyproc (saint gobain)/ India Gypsum/Armstrong) Providing and fixing suspended false ceiling including steps as per design with 12.5mm tapered edge Gyproc / 12mm thick Elephant Gypsum Board (Makes-Gyproc (saint gobain)/ India Gypsum) to the grid comprising of cold rolled galvanized metal section to the required line and level. The grid consisting of a perimeter channel(MF6a of dimension 20mmX27mmX37X3.5m) fixed round the perimeter to receive and of the ceiling section (MF5) and outer edge to gyp-board. The intermediate channel (MF7 of dimension 15mmX45mmX0.9mmX3.5M) at 1200mm c/c in the one direction and the ceiling section (MF5 of dimension 80mmX26mmX0.5mX3.5M) at 450mm c/c in the other direction to be connected by a connecting clip. The grid to be suspended with an adjustable strap hanger(MF8) of dimension 25mmX9.5mm at 1200mm c/c on both ways from the structural soffit and expandable The Gypsum Board (Makes-Gyproc (saint gobain)/ India Gypsum/Armstrong) layers to be screwed to the M/F ceiling sections with gyp-board dry wall screws. Jointing and screw spotting are then carried out as per manufacture's standard recommendation. Perimeter Channels (MF7) to be used around the cuts outs for light fittings, A/C ducting etc. The work should be complete as per instruction of architect or engineer in charge including 2-3 coats of oil bound distemper over a coat of primer. The rate should be inclusive of making opening with frame etc. For electrical/air conditioning, A.C grill etc. if required and finishing of ceiling in all respect. payment shall be made only for exposed surface & actual measurement at site. The work includes cost and conveyance of material and labour charges including all operational charges tools lift and all height etc Note: No deduction for Light	650.00	Sq.ft		
b	Cove as per Detail Making 200 mm deep cove as/detail in gyboard and POP in architectural features including curved / designer as per Architect's approval.. The rate shall be inclusive of necessary framework, making cutout for light fixtures, bulkheads etc. complete	25.00	R.ft		
c	False Ceiling (Armstrong) Providing & fixing in position false ceiling in Mineral Fibre Armstrong Tile 600 x 600 mm x 16 mm of type Dune Tegular- RH 99 Prima tile Grid System (framework) as specified by Armstrong Co. with suspenders /Hangers of G.I. Wire with roof plugs wherever required. Making necessary framework for A.C ducting, if any, and necessary cutouts for diffusers and light fittings, taping and finishing to proper line & level including making grooves and trap doors for A.C unit including finishing with White Plastic Emulsion Paint etc. complete in	260.00	Sq.ft		
5 FURNITURE Work					
a	BRANCH MANAGER TABLES WITHOUT SIDE CREDENZA (Finishing with 1mm thick Laminate) (a) Providing and fixing at site, Branch Manager table (As per Picture and Detail drawings) made of 19mm th. commercial ply (Makes-Century/Green ply/Archid) with 1mm thick laminate (Make- Archidiam/Century/Greenlam) of desired shade, design on outer visible surfaces; single color on horizontal & vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. CP TEAK wood lipping will be provided on all the edges of the table, including PU Polish and bottom touching the floor and the drawers (b) The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 19mm commercial ply fixed with sliding telescopic channels (Makes-Hettich / Haffele/ Godrej/Ozone) of approved make. (c) All other surfaces i.e. inside / legsapce of table, inside of drawer /cupboard shall be provided with 0.8mm thick laminate(Make-Archidiam/Century/Greenlam) of desired shade/design and gloss, and wood lipping / beading. The table shall have a CPU ledge made of 19mm thick Commercial Ply on one side, complete as per drawing.				
	Branch Manager Table (6'-0"x3'-0"x2'-6")	1	Nos		
b	OFFICER AND CLERK TABLE (a) Providing and fixing at site, officer/ Clerk table made of 19mm th. commercial ply (Makes-Century/Green ply/Archid) with 1mm thick laminate (Make- Archidiam/Century/Greenlam) of desired shade, design on outer visible surfaces; single color on horizontal & vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. CP TEAK wood lipping will be provided on all the edges of the table, including PU Polish and bottom touching the floor and the drawers. (b) The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 19mm commercial ply fixed with sliding telescopic channels (Makes-Hettich / Haffele/ Godrej/Ozone) of approved make. (c) There shall be provision of one storage cabinet 1'-3" wide. The frame shall be made with 19mm thick commercial ply. The cabinet shall have Three lockable drawer running on side mounting drawer slides (channels) (Makes-Hettich / Haffele/ Godrej/Ozone) of approved make & one cupboard with shutter beneath the drawer, made of 19mm thick commercial ply finished with 1mm thick laminate (Make- Archidiam/Century/Greenlam) of desired shade & design. All fitting / accessory shall be of approved make. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick Commercial Ply. (Makes-Century/Green (d)The work shall also include provision of foot rest made with Sal wooden member of section 3" x 1.5" across the leg space. (e) All other surfaces i.e. inside / legsapce of table, inside of drawer /cupboard shall be provided with 0.8mm thick laminate(Make-Archidiam/Century/Greenlam) of desired shade/design and gloss, and wood lipping / beading. The table shall have a CPU ledge made of 19mm thick Commercial Ply on one side, complete as per drawing. (f) The work shall also include provision of Profile Lights in front of Counter/ Tables				
	Officer Table (5'-0"x2'-6"x2'-6")	2	Nos		
	Clerk Table (4'-0"x2'-6"x2'-6")	1	Nos		
c	Cash Counter- Providing and fixing Cash Counter with 2'-6" wide staff working counter at 2'-6" height from FFL and 1'-6" wide customer ledge at 3'-6" height from FFL. The structure shall be made using 19mm commercial board of (Makes-Century/Green ply/Archid) and finished with 1 mm thick laminate of (Make- Archidiam/Century/Greenlam) Make, shade as approved. Including cost of sliding key board tray on sliders, three pulout drawer on sliders of width 40cm and a bottom rack for CPU shall be provided. Locks, SS handle, auto closing hinges & SS footrest (2" thick) shall be provided. All inside surface are to be finished with 0.8 mm thick laminate. Table edges are to be finished with t.w. moulding duly polished etc. complete in all respects to the entire	5	R.ft		
d	Cash cabin Facia - Providing & fixing 1"x2" beading finished with PU Polish along the toughened glass (as per design) for Cash Cabin facia. Horizontal band shall be provided on the facia below the working top made with 18mm thick plywood finished with 1 mm thick laminate. Portion below the horizontal band shall be finished with 6mm thick CNC HDHMR Board (as per design) finished with Royale Matt PU Polish of approved shade with groove pattern as per instructions of Bank's Architect/Engineer in charge	1	Nos		
e	Reception Table of size (4'-0"x2'-0"x2'-6") (Providing and fixing at site reception table made of 19mm thk. Commercial ply with 1 mm thk laminate of desired shade and with front vertical surface pasted with fluted MDF. CP Teak wood lipping will be provided on all edges of the table, including PU polish. The work shall also include provision of Profile Lights in front of Counter/ Tables, and There shall be provision of one storage cabinet 1'- 3" wide. The frame shall be made with 19mm thick commercial ply. The cabinet shall have Three lockable drawer running on side mounting drawer slides (channels) (Makes-Hettich / Haffele/ Godrej/Ozone) of approved make & one cupboard with shutter beneath the drawer, made of 19mm thick commercial ply finished with 1mm thick laminate (Make- Archidiam/Century/Greenlam) of desired shade & design. All fitting / accessory shall be of approved make. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick Commercial	1	Nos		
f	Side Credenza :- made of 19mm thick commercial ply (Makes-Century/Green ply/Archid) frame and 6mm thick commercial ply on back side & 1.0M Thick Laminate (Make- Archidiam/Century/Greenlam) on top horizontal surface , one vertical visible side only, and 0.8mm thick laminate on inside. All exposed edges shall be covered with C.P teak wood lipping. The credenza will have drawers shall be provided on drawer slides(channels size 1'-4") (Makes-Hettich / Haffele/ Godrej/Ozone)of approved make. The sides of the drawer shall be made of 12mm thick Commercial Ply (Makes-Century/Green ply/Archid) (bottom of 6mm thick plywood & front of 19mm thick Commercial Ply (Makes-Century/Green ply/Archid). The remaining part of the credenza will be cupboard with shutters and one shelf. All the internal surfaces shall be finished with 0.8mm thick mica(Make-Archidiam/Century/Greenlam)of desired shade, design, gloss. All the exposed wooden surfaces shall be malamine polished in desired shade as per specifications given in item 2.1 (c). Hardware- 4" handle (4nos) Locks (2nos), hinges (4Nos), Magnetic catcher. complete with all fittings in confirmation to the drawing				
	CREDENZA Size (2'-6"x1'-6"x2'-6") (For Officer)	2	Nos		
6.0 LOW HEIGHT STORAGE CABINETS /BACK STORAGE: (2'-6" HIGH) for Manager Cabins.					

a) Providing and fixing Low Height storage cabinets of size 2'-6"(High)x 1'-6"(Deep) along the walls/partitions, as per interior drawings,using 19mm Commercial Ply (Makes-Century/Green ply/Archid) for shutters, vertical and horizontal partitions, 6mm Commercial ply for the back side. Finishing with 1.0 mm thick Laminate (Makes- Archidiam/Century/Greenlam) of approved shade on top, vertical and horizontal visible surfaces and 0.8mm thick laminate on inside.The shutters shall be overlapping on the carcass and shall be provided with suitable hinges with autoclose & soft close. The width of the shutter shall be between 12" to 15" as per the site conditions. All the internal surfaces shall be finished with 0.8mm thick mica(Make- Archidiam/Century/Greenlam)of desired shade, design, gloss. All the exposed wooden surfaces shall be malamine polished in desired shade as per specifications given in item 2.1 (c). The cabinet shall be complete with 4" handles, knobs, locks, Hings and	22.00	Sq.ft		
b LOW HEIGHT STORAGE CABINETS /BACK STORAGE: (4'-0" HIGH) BEHIND THE WORKSTATION .				
(a) Providing and fixing Three lockable drawer Low Height storage cabinets of size 3'-6"(High)x 1'-6"(Deep) along the walls, as per interior drawings, running on side mounting drawer slides (channels) (Makes-Hettich / Haffele/ Godrej/Ozone) of approved make. Storage made of 19mm Commercial Ply (Makes-Century/Green ply/Archid) for Drawer Front, vertical and horizontal. 6mm Commercial ply for the back side. Finishing with 1.0 mm thick Laminate (Makes- Archidiam/Century/Greenlam) of approved shade on top, vertical and horizontal visible surfaces and 0.8mm thick laminate on inside.The shutters shall be overlapping on the carcass and shall be provided with suitable side mounting drawer slides autoclose & soft close. All the internal surfaces shall be finished with 0.8mm thick mica(Make- Archidiam/Century/Greenlam)of desired shade, design, gloss. All the exposed wooden surfaces shall be malamine polished in desired shade as per specifications given in item 2.1 (c). The cabinet shall be complete with 4" handles, knobs, locks and magnet catchers (Makes- Godrej/ Dorset/ Dorma) etc.to the satisfaction of the Architect/Engineer.	140.00	Sq.ft		
c SHUTTERS BELOW GRANITE COUNTERS				
Providing and fixing Below Granite Counter Storage cabinets of size 2'-6"(High) along the Pantry walls, as per interior drawings,using 19mm Commercial Ply (Makes-Century/Green ply/Archid) for shutters, vertical and horizontal partitions, 6mm ply for the back. 1 mm thick laminate (Make- Archidiam/Century/Greenlam) of approved shade on top, vertical and horizontal visible surfaces. The shutters shall be overlapping on the carcass and shall be provided with suitable hinges with autoclose & soft close. The width of the shutter shall be between 12" to 15" as per the site conditions. All the exposed edges of the ply shall be provided with wooden lipping 19mm x 3mm,duly including PU Polished in desired shade.The inner surface shall be provided with 0.8mm thick laminate(Make- Archidiam/Century/Greenlam) of desired shade, design and gloss. The cabinet shall be complete with handles, knobs, locks and magnet catchers (Makes- Godrej/ Dorset/ Dorma) etc.to the satisfaction of the Architect/Engineer.	12.00	Sq.ft		
d WOODEN BOXING FOR THE ELECTRICAL PANEL				
Providing and fixing at site wooden boxing for the electrical panel as per the design and drawing. The carcass shall be made of 19mm thick commercial ply Finishing with 1mm thick laminate desired shade design and gloss of approved makes. Wooden molding, lipping etc.should be provided wherever required as per drawing in desired shade. . The work shall also include the cost of making cutouts for the electrical switches, lights, switch boxes etc. The carcass shall have intermediate band and skirting of 1mm thick Laminate of desired shade, design and gloss. The shutter shall be mounted on the SS Piano hinges and provided with magnetic catcher, lock and tower bolts as required etc. All the visible edges of board shall be provided with 4mm thick teak wood lipping with PU Polish. All interior surfaces and back of shutters shall be provided with 0.8mm thick mica. the cabinet shall be complete with all necessary hardwares like locks,handles, catchers, towerbolts etc. Measurement will be done for front surface	40.00	Sq.ft		
7 Flooring				
FLOOR TILES- Providing and laying Full body Vitrified tiles in flooring including 100mm high skirting (Basic rate of tile is Rs. 90/- per Sq.ft.) of homogeneous composition of size 597mm x 597mm (thickness to be specified by the manufacturer) with water absorptions less than 0.08% and confirming to IS :15622 of approved shade and pattern. Tile to be laid on 20 to 50 mm thick cement mortar 1:4 (1 cement : 4coarse sand) including filling the joints with epoxy/ white cement slurry mixed with pigment to match the shade of the tile, leveling of floor if required, covering it with plaster of paris to avoid damages & complete cleaning prior to handing over. Including cost of Tiles Adhesive/ tile chemical .All complete as per drawing, approval and instructions of the Engineer Incharge/Architect. Flooring – Ivory/Offwhite Vitrified tiles (Make : H R Johnson / Somany / RAK / Kajaria) (Model No Kajaria Tiles	1000.0	Sq.ft		
8.0 Pin Up Board				
providing and fixing 12 mm thick soft board over 12 mm thick commercial ply (Makes-Century/Green ply/Archid) fixed in wooden frame made out of commercial champ wood out of size 2.5 " x 1.5" (duly polished). The work shall be completed by covering the soft board with fabric of approve shade.(basic rate of Cloth to be Rs. 1200/- Sq.Mtr.)	12	Sq.ft		
b) Providing & fixing of PSB Signage made of 3mm Acrylic sheet with LED Panels for Back light of logo of size (2'x3') behind Reception Table complete as approved by Bank's Architect/Engineer In-charge.	1	Nos		
C TABLE TOP GLASS :- Providing and supplying 8 mm thick light clear float toughened glass with its edges duly bevelled & grinded on all sides	30.000	Sq.ft		
d SUGGESTION BOX (450 x 600 x 200) : Providing and fixing suggestion box made out of 19mm BWP ply and finished with 1mm laminate and enamel painted on the inside. A 300 mm long slit is to be made in the front for letters, etc. The work should be completed in all respects.	1	Nos		
e WRITING LEDGE - P/F Writing ledge made BWP box of size 900 mm x 300 mm x 200 height finished with 1 mm thick mica with a provision of 4 nos divisions for voucher and 12 mm glass on top fixed with 3" high SS spacers (BRANCH)	1	Nos		
f CHEQUE DROP BOX - P/F one cheque drop box made out of 12 mm thick BWP duly laminated with all hardware fitting and fixtures. Size 400 x 300 x 100 mm	1	Nos		
9 DISMANTLING WORK				
a) Dismantling All Existing aluminium/ wooden partitions, doors, windows, fixed glazing and false ceiling table and counters including disposal of unserviceable material.	1	Job		
b) Dismantling and Removing & Fix of Rolling Shutters & Collapsible Gate etc.	1	Job		
c) Providing and fixing Pantry Slab Granite SS sink including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels.Granite of any colour and shade Including cost of edge moulding to 18 mm thick marble stone counters, Vanities etc.	4.0	Rft		
.....				
INTERIOR FURNISHING WORK				
G.S.T as applicable will be paid extra by the bank				